

# LDK data sheet


## The cassette wrench 160 - 24000 Nm



### Precise. Flexible.

- » Small dimensions and compact design for confined spaces
- » An integrated pressure relief valve ensures a safer working environment
- » Generously sized oil channels in device, provide minimal heating under continuous load
- » Various inserts available as an accessory, for flexible working
- » Pushpin technology allows simple reconnection and changing the cassette

### Technical data

Type	Nm min/max <sup>*1</sup>	lbf·ft min/max <sup>*1</sup>	⊘ mm	⊘"	B <sub>1</sub> mm	B <sub>2</sub> mm	E mm	F mm	H mm	H <sub>1</sub> mm	L mm	R mm	 <sup>*2</sup>
LDK - 3	160 - 3300	120 - 2400	32 - 60	1 1/4" - 2 3/8"	28	40	137	145	39.2	91/103	205	28 - 48	1.6
LDK - 6	350 - 6200	260 - 4500	41 - 80	1 5/8" - 3 1/8"	35	50	156	172	39.2	115/130	247	34 - 60	2.4
LDK - 12	550 - 12500	410 - 9200	55 - 100	2 3/16" - 3 7/8"	47	65	200	215	39.2	141/156	311	46 - 73	4.4
LDK - 24	1200 - 24000	880 - 17700	80 - 130	3 1/8" - 5"	56	82	245	260	50.0	182/202	385	62 - 96	8.2

<sup>\*1</sup>Maximum torque at 800 bar

<sup>\*2</sup>Without exchangeable cassette

All rights reserved. Subject to modifications without prior notice.

